

[Web](#) [Images](#) [Videos](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more](#) ▼

[Sign in](#)

Google scholar

rssl adc gaussian zero mean

Search

[Advanced Scholar Search](#)

[Scholar Preferences](#)

Scholar [All articles](#) [Recent articles](#)

Results **1 - 10** of about **347**. (0.11 sec)

A RSSI-Based Cooperative Anomaly Detection Scheme for Wireless Sensor Networks

J Tang, P Fan - ... , Networking and Mobile Computing, 2007. WiCom ..., 2007 - [ieeexplore.ieee.org](#)

... **RSSI**) output that is sampled by a 10-bit **ADC**. ... where, **RSSI**(d) is the **RSSI** value recorded at distance d ... path loss exponent, and $X \sigma$ is a **Gaussian** random variable ...

[Cited by 3](#) - [Related articles](#) - [All 2 versions](#)

Apparatus and Method for Measuring Received Signal Strength Indicator, and Recording ...

CI Yeh, HS Lim, DS Kwon - US Patent App. 10/588,101, 2004 - [Google Patents](#)

... accumulated result; and a computer system estimating an **RSSI** of the ... functions at input and output signals of the **ADC** are approximately **Gaussian** with **zero** ...

[All 4 versions](#)

[PDF] *Mobility-Assisted Position Estimation in Wireless Sensor Networks

H Chen, P Huang, HC So, K Sezaki - Proceedings of the 2008 14th IEEE International ..., 2008 - [ee.cityu.edu.hk](#)

... which signal decays), and σX a **zero-mean Gaussian** random vector (in dB) with standard ...

This is the **RSSI** signal that has a dedicated **ADC** channel (channel 0 ...

[Related articles](#) - [View as HTML](#) - [All 3 versions](#)

Detection of Sybil Attack in Beacon Enabled IEEE802. 15.4 Networks- *202.194.20.8 [PDF]

F Amini, J Misic, H Pourreza - ... and Mobile Computing Conference, 2008. IWCMC'08. ..., 2008 - [ieeexplore.ieee.org](#)

... standard deviation of the **Gaussian** distribution ... provides a **RSSI** output that is sampled by an 8-bit **ADC**. The **RSSI** is mainly used for RF signals, and the estimate ...

[Related articles](#) - [All 2 versions](#)

Self localization of wireless sensor nodes by means of autonomous mobile robots- *unipd.it [PDF]

A Zanella, E Menegatti, L Lazzaretto - Proceedings of the 19th Tyrrhenian International ... - Springer

... distribution of this factor is generally assumed to be **Gaussian**, with **zero** ... is converted in digital form by a linear **ADC** with 16 ... P_i (dBm) = **RSSI** 14 - 114

[Cited by 1](#) - [Related articles](#) - [All 3 versions](#)

An integrated baseband processor for universal personalcommunications applications

DE Fague - Third IEEE International Symposium on Personal, ..., 1992 - [ieeexplore.ieee.org](#)

... This circuit digitizes the incoming **RSSI** signal (output from ... savings is achieved by powering the **ADC** for a ... This includes **Gaussian** BbT = 0.5 filters for Digital ...

Calibration and Measurement of Signal Strength for Sensor Localization

N Patwari, P Agrawal - Localization Algorithms and Strategies for Wireless ..., 2009 - [books.google.com](#)

... Radio Channel RSSI **RSSI** Circuit **ADC** Pathloss Estimation ... Transmit power battery variations • Receiver **RSSI** circuit device ... to be random, and **Gaussian**, with a ...

B Kusy, G Balogh, J Sallai, A Ledeczki, M ... - Lecture Notes in Computer Science, 2007 - Springer
... as 8 MHz micro- controller, 9 kHz **ADC** sampling, 4 kB ... signal by analyzing the signal
at the **RSSI** pin of ... distribution of q-ranging errors is not **Gaussian**, but it ...
[Cited by 14](#) - [Related articles](#) - [BL Direct](#) - [All 12 versions](#)

AJ Leeuwenburgh, JWF Ier Laak, AG Mulders, ... - 2003 IEEE International Solid-State Circuits ..., 2003 - ieeexplore.ieee.org

... In transmit mode, the **Gaussian** shaped input data stream ... A single 8b **ADC** [3] sampling at 10.368 ... The received signal strength indicator (**RSSI**) output, computed ...

[Cited by 8](#) - [Related articles](#) - [All 4 versions](#)

